# **SONAR**

### **DECORATIVE INDOOR WALL SCONCE**

# **Elegant Contoured Design** Hardwired LED or E26 Medium Base Sockets

0	0 . 7.	
CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		

We reserve the right to revise the design or components of any product without notice.

#### SPECIFICATIONS .

- APPLICATIONS Restaurants, Dining, Foyers, Hallways, Retail, Commercial, Hospitality, Restrooms, Conference Rooms, Theaters, Hallways, Corridors, Libraries, Assisted Living, Nursing Homes, Hotels, and Motels.
- DIMENSIONS Small: 13.5"H x 5"W x 5"D (4.75"Dia. Cover)
  - Large: 21"H x 5.5"W x 5"D (4.75"Dia. Cover)
- DRIVER 120 Volt Driver featuring TRIAC Dimming (for Hardwired LED)
- HOUSING Durable cold rolled steel.
- FINISH Powder Coat Finish applied over pre-treated surfaces.
- LIGHT ENGINE Energy Efficient LED (Hardwired) or E26 Medium Base Sockets for LED screw-in bulbs (A15/A19). Sockets allow you to add your own LED or Incandescent Light Bulbs - Max 10W Per Socket.
- MOUNTING Wall mounted via universal J-Box strap.
- · COMPLIANCE Built to comply with U.S. and Canadian Safety Standards. Suitable for Indoor Locations Only.



ORDERING INFO \_\_\_

	Series	Size	Wattage	CCT	Voltage	Finish	Options
<b>ORDERING GUIDE:</b>							

#### **SERIES**

**SN** = Sonar Series

### **SIZE**

S = Small 13.5"H x 5"W x 5"D (4.75"Dia. Cover)**L** = Large 21"H x 5.5"W x 5"D (4.75"Dia. Cover)

\*Note for SCCT: Fixtures will ship from factory at the warmest CCT. It is the installer's responsibility to set the fixture at the desired CCT for their project.

#### **WATTAGE / LAMPING**

#### **Hardwired LED**

**UP10** = 10 Watt LED Uplight | 980 Lumens at 4000K (90CRI) **DN10** = 10 Watt LED Downlight | 980 Lumens at 4000K (90CRI) UP10/DN10 = 10 Watt LED Uplight and 10 Watt LED Downlight

— 1960 Total Lumens (Up/Down) at 4000K (90CRI)

## Add Your Own Lamping (120V Only)

**MBS** = Medium Base Sockets (Lamps by Others)

- Base Type: E26 Medium Base
- Bulb Type: A15 (Size Small) or A19 (Size Large)
- Max Wattage: Max 10W Per Socket

## COLOR TEMPERATURE (Hardwired LED Only)

**SCCT** = \*Selectable CCT: 2700K | 3000K | 3500K | 4000K | 5000K

#### VOLTAGE (Hardwired LED Only)

120 = 120 Volt Driver

- Features TRIAC Leading-Edge Dimming

## STANDARD FINISH

BK = Black  $\mathbf{WH} = White$ 

#### **PREMIUM UPCHARGE FINISH**

RAL# = RAL Color Finish

- Example: RAL3017 (ROSE)

## **OPTIONS**

**PCH** = Pull Chain Switch (ON/OFF)

PS = Push Switch (ON/OFF)

## SELECTABLE CCT (Hardwired LED Only) -







For Sonar Small (Lamps by Others) (Lamps by Others)

For Sonar Large

