

# Cannes 2

## FULL CUT-OFF SERIES

Low Height Wall Mount — 2 Sizes  
LED



Cannes 2 Style A: Flat Lens



Cannes 2 Style B: Bubble Lens

We reserve the right to revise the design or components of any product without notice.

**ARRA**  
Compliant

CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		

### SPECIFICATIONS

- BACKPLATE — Die cast aluminum.
- DRIVER — EBU is Standard.
- EMERGENCY — LED — Remote.
- GASKETING — High temperature, non-aging black EPDM and/or neoprene rubber concealed in housing pocket and enclosed by cast-in drip shield and rear wire entrance hole to protect against outside contaminants.
- HOUSING — Die cast aluminum with concealed mounting plate. Standard finish is Bronze oven baked Polyester Powder Coat.
- LENS — Specify Flat or Bubble Lens.
- REFLECTOR — 032 Prescription Specular aluminum for high efficiency and reduce arc tube voltage rise.
- UL/ULC Listed to U.S. and Canadian safety standards. Suitable for wet locations.

LAMP TYPE/QTY/WATTAGE <sup>1</sup>			
Visit <a href="http://www.eclipselightinginc.com">www.eclipselightinginc.com</a> for available IES files			
Fixture	CANNES 2		
Lens Style	Small	Medium	
Dimensions - W x H x D	8" x 5" x 4"	9.5" x 6" x 6"	
Light Emitting Diode	LED	16 or 28w	35 or 45w

### ORDERING GUIDE:

Series	Style	Lamp Type/Qty/Watt	Voltage: Primary/Emergency	Finish	Options
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

#### NOTES:

- Consult Factory with requests regarding lamp sources, including LED, color temp., wattages or voltages not shown.
- Consult Factory for additional Emergency Battery options. Max WHIP length with the REL provided by the factory is 8 feet.
- Consult Factory for other Voltage
- Due to form and fit, final selection of the Battery Pack under discretion of Factory

**SERIES**  
CN2 = Cannes 2 Series

**SIZE**  
S = 8" x 5" x 4"  
M = 9.5" x 6" x 6"

**LENS**  
A = Flat Lens  
B = Bubble Lens

**LAMP TYPE/QUANTITY/WATTAGE**  
Refer to Chart Above

**COLOR TEMP (LED)**  
3K = ±3000K range LED  
4K = ±4000K range LED  
5K = ±5000K range LED  
6K = ±6000K range LED

**VOLTAGE**  
347 = 347 Volts EB  
EBU = High Temp Universal Volt (120-277V)

**FINISH**  
BK = Black  
BZ = Bronze Standard  
PNA = Painted Natural Aluminum  
WH = White

**OPTIONS**  
9206 = Photocell – 120V  
9221 = Photocell – 277V  
FUS = Single Fusing  
DFUS = Double Fusing

**EMERGENCY BATTERY OPTIONS<sup>3 50 52 53</sup>**  
*No onsite Emergency Power (AC or DC) is provided*  
*Specify Fixture Voltage: 120V or 277V Power Feed*  
A=120V or B=277V  
**LED Emergency Battery**  
REL82 = Remote: LED 4W (Fulham)—Factory Recom'd