

Hanover 2

Durable Low Profile Wall Pack
Selectable Lumen Output / CCT
Wet Location Listed

We reserve the right to revise the design or components of any product without notice.

CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		

SPECIFICATIONS

- APPLICATIONS — Storage areas, shopping area walkways, entryway, and low level security.
- DRIVER — Universal voltage (120-277V), electronic driver is standard (NON-Dimming).
- HOUSING — Two-piece die cast aluminum housing with built-in thermal conductive LED panel for optimal heat management.
- LENS — Anti-UV prismatic translucent lens for reduced glare and uniform light distribution.
- FINISH — Chip and fade resistant powder coat finish.
- MOUNTING — Mounting bracket for easy installation to standard 4" or 5" electrical J-BOX. (3)1/2" K.O. holes on three sides allow for surface conduit entry.
- LIGHT ENGINE — Energy efficient LED. Integral Controller allows for Selectable Lumen Output/CCT.
- OPERATING TEMPERATURE — -40°C to 40°C (-40°F to 104°F)
- COMPLIANCE — Built to comply with U.S. Safety Standards. UL/cUL Wet Location listed. Suitable for applications requiring 3G testing per ANSI C136.31.
- WARRANTY — 5-Year Limited Warranty.



ORDERING INFO

Series	Wattage	CCT	Voltage	Finish	Options
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

SERIES

HN2 = Hanover 2 - Selectable Series

WATTAGE

Note: Lumen Output can be adjusted via Integral Controller. See Chart below for Wattage / Lumen Output.
 LED65 = *65 Watt LED
 LED100 = *100 Watt LED

COLOR TEMPERATURE (CCT)

SCCT = *Selectable CCT: 3000K | 4000K | 5000K

*Note: Fixtures will ship from factory at lowest wattage and warmest CCT. It is the installer's responsibility to set the fixture at the desired wattage and CCT for their project.

VOLTAGE

UNV = Universal Volt (120-277V) Electronic Driver

FINISH

BK = Black
 BZ = Bronze
 WH = White

PHOTOCELL OPTION

9328 = Photocell Button (120/277V)

EMERGENCY / BATTERY OPTIONS

EL8W = 8 Watt Integral Emergency Battery
 — 900 Lumen / 90min Battery Backup Time
 — Note: Available for 65W Only

Performance Data

System Watts	Voltage	CRI	Lumens (3000K)	LPW (3000K)	Lumens (4000K)	LPW (4000K)	Lumens (5000K)	LPW (5000K)
65w	120~277V	70	9500lm	146 lm/W	10000lm	154 lm/W	9800lm	151 lm/W
100w	120~277V	70	14800lm	148 lm/W	15500lm	155 lm/W	15000lm	150 lm/W

Selectable Lumen Output

Setting	Voltage	65 Watt		100 Watt	
		System Watts	Lumens (5000K)	System Watts	Lumens (5000K)
100%	120~277V	64.93	9557.10	103.20	14850.00
80%	120~277V	49.30	7894.16	84.21	12640.32
60%	120~277V	34.47	5973.19	61.92	9484.70
40%	120~277V	23.37	4224.24	42.83	6623.10

Hanover 2


Durable Low Profile Wall Pack
Selectable Lumen Output / CCT
Wet Location Listed

We reserve the right to revise the design or components of any product without notice.


CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		

DIMENSIONS

65 Watt Model



100 Watt Model



FEATURES



Photocell (Optional)
 Adding a photocell provides energy efficiency and security/safety.

Housing

Two-piece die-cast aluminum housing with built-in thermal conductive panel for optimal heat dissipation which increases LED efficiency and extends operational lifetime.

Optics

Anti-UV prismatic translucent lens for reduced glare with zero uplight distribution which maximizes light efficiency and illumination.



Mounting

Mounts directly over a standard 4" or 5" J-Box. Three 1/2" K.O. holes on three sides allows for surface conduit entry.



Emergency Battery (Optional)

Integral Emergency Battery
 8 Watt / 900 Lumen / 90min.



Power / CCT Controller

Lumen Output & CCT can be adjusted via the integral controller switch.

