

Liverpool 5

Full Cutoff Wall Pack Luminaire

Selectable Wattage / CCT

Wet Location / IP65 Rated

We reserve the right to revise the design or components of any product without notice.

CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		

SPECIFICATIONS

- DRIVER — Universal Voltage (120-277v) electronic driver with 0-10V dimming.
- HOUSING — Die-cast aluminum with built-in heatsink, fully sealed by silicone ring that prevents dust and other contaminants from entering.
- FINISH — Polyester powder coated finish.
- LENS — U.V. stabilized polycarbonate lens for uniform illumination.
- LIGHT ENGINE — Energy efficient LED featuring Selectable Wattage/CCT.
- LIFETIME — 50,000+ Hour LED Life Expectancy (L70).
- MOUNTING — Mounts to standard 4" J-BOX.
- OPERATIONAL TEMP — -40°F to +113°F.
- PHOTOCELL — Photocell is standard.
- COMPLIANCE — Built to comply with U.S. and Canadian Safety Standards.
DLC 5.1 Compliant. UL listed for Wet Location, IP65 Rated.
- WARRANTY — 5-Year Limited Warranty.



ORDERING INFO

ORDERING GUIDE:	Series	Wattage	CCT	Voltage	Finish	Options
------------------------	---------------	----------------	------------	----------------	---------------	----------------

SERIES

LV5 = Liverpool 5 Series

WATTAGE

Refer to Below Chart for Wattage / Lumen Output

SLED-L = *Selectable Wattage - Low: 40W | 60W | 80W

SLED-H = *Selectable Wattage - High: 80W | 100W | 120W

COLOR TEMPERATURE (CCT)

SCCT = *Selectable CCT: 3000K | 4000K | 5000K

*Note: Fixtures will ship from factory at lowest wattage and warmest CCT. It is the installer's responsibility to set the fixture at the desired wattage and CCT for their project.

VOLTAGE

UNV = Universal Volt (120-277v) Driver

STANDARD FINISH

BZ = Bronze Finish

PREMIUM UPCHARGE FINISHES

BK = Black Finish

PNA = Painted Natural Aluminum

WH = White Finish

SLED Model	SLED-L			SLED-H		
Wattage	40W	60W	80W	80W	100W	120W
Lumens	5,200	7,800	10,400	10,400	13,000	15,600

DIMENSIONS

