

Clark Shallow (ADA)

Low Profile Luminaire
Selectable Wattage & CCT
Indoor Ceiling or Wall

We reserve the right to revise the design or components of any product without notice.

CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		

SPECIFICATIONS

- **DIFFUSER** — Opal white polycarbonate is standard.
- **DRIVER** — Universal Volt (120~277V) Electronic Driver. 0-10V Low Voltage Dimming (100% to 30%) is Standard.
- **FINISH** — Polyester powder coat white Standard. Optional Custom Colors.
- **GASKETING** — High temp, non-aging black EPDM gasketed seal. Seals diffuser to cast housing to protect against outside contaminants.
- **HOUSING** — Spun aluminum housing with built-in heatsinks for thermal management.
- **MOUNTING** — Indoor Surface, Wall or Ceiling.
- **COMPLIANCE** — Built to comply with U.S. and Canadian Safety Standards.

Build America/Buy America Act (BABA), Buy American Act (BAA), and ADA compliant.



ORDERING INFO

Series	Wattage	CCT	Voltage	Finish	Options

ORDERING GUIDE:

SERIES

CK-S = Clark Shallow Series

WATTAGE

Refer to Below Chart for Wattage / Lumen Output

SLED = Selectable LED Wattages: 21W | 28W

COLOR TEMPERATURE (CCT)

SCCT = Selectable CCT: 3000K | 3500K | 4000K | 5000K

VOLTAGE

UNV = Universal Volt (120-277v) Electronic Driver

STANDARD FINISH

BK = Black Finish
 BZ = Bronze Finish
 PNA = Painted Natural Aluminum
 WH = White Finish Standard

PREMIUM UPCHARGE FINISH

CC = Custom Color (Visit www.ralcolor.com)
 — Provide RAL# or Make-to-Match Color Chip
 +NAT = Conformal Coating - Light Engine Only

CONTROL OPTIONS

Sensor Control (Sensor Integral to Fixture)
OCC = Occupancy Sensing | Motion Sensor Integral[Ⓜ]
 — Microwave / Single Feed / 120/277V Only
 — Standby Dim Level Presets: ON/OFF (0%/100%)

MISC. OPTIONS

FUS = Single Fusing

ACCESSORY OPTIONS (order as a separate line)

9002 = Tamperproof Screwdriver
 REMT = Remote Controller for Sensor Options

NOTES:

[Ⓜ] Max mounting height of fixture is 18' (18 feet)

WATTAGE / LUMEN INFORMATION

Wattage	CCT	Lumens	Efficacy
21 Watt	3000K	3,100 Lumens	148 lm/W
	3500K	3,125 Lumens	149 lm/W
	4000K	3,150 Lumens	150 lm/W
	5000K	3,200 Lumens	152 lm/W
28 Watt	3000K	4,100 Lumens	144 lm/W
	3500K	4,125 Lumens	145 lm/W
	4000K	4,150 Lumens	146 lm/W
	5000K	4,200 Lumens	147 lm/W


Clark Shallow (ADA)

Low Profile Luminaire
Selectable Wattage & CCT
Indoor Ceiling or Wall



We reserve the right to revise the design or components of any product without notice.

CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		



DIMENSIONS



**Clark Shallow
Series Mounting**



SELECTABLE LED WATTAGE/CCT



Selectable LED Wattage/CCT Switches
Located on LED Board