# **Horizon 3**

# **Indoor Ceiling Fixture** Selectable CCT LED Board **RoHS Compliant / Indoor Damp Location**

we reserve the right to revise the design of components of any product without notice.					
CATALOG #		TYPE			
PROJECT/LOCATION					
APPROVED BY					

#### SPECIFICATIONS -

- DRIVER 120V electronic driver with 0-10V dimming.
- DIFFUSER High Transmission Opal Acrylic for evenly diffused light distribution.
- HOUSING Die-formed cold rolled steel.
- FINISH Black Matte or Brushed Nickel Finish.
- LIGHT ENGINE Energy Efficient LED with Built-in Switch for Selectable CCT (90CRI).
- MOUNTING Flush mount to ceiling.
- OPERATIONAL LIFETIME 50,000 Hours
- OPERATING TEMP -20°C to 40°C | -4°F to 104°F
- COMPLIANCE Built to comply with U.S. and Canadian safety standards. ETL/cETL and California T24 Listed. FCC and RoHS Compliant. Suitable for Indoor Damp Locations.
- WARRANTY 3-Year Limited Warranty





## ORDERING INFO

	Series	Size	Wattage	CCT	Voltage	Finish	Options
ORDERING GUIDE:							

#### **SERIES**

**HOR3** = Horizon 3 - Selectable CCT Series

14 = 14" Diameter x 3.75" Height 17 = 17" Diameter x 3.75" Height

## **LED WATTAGE**

LED25 = LED 25 Watt

#### **LED COLOR TEMPERATURE (CCT)**

SCCT = \*Selectable CCT: 3000K | 4000K | 5000K

\*Note: Fixtures will ship from factory at warmest CCT. It is the installer's responsibility to set the fixture at the desired wattage and CCT for their project.


#### **VOLTAGE**

120 = 120 Volt Electronic Driver

# **FINISH**

BK = Black Matte **BN** = Brushed Nickel

## **DIMENSIONS/WATTAGES** .



SIZE	DIMENSIONS	WATTAGE	LUMENS (3000K)	LUMENS (4000K)	LUMENS (5000K)
14	14" Diameter x 3.75" Height	25 Watt	2000 Lumens	2250 Lumens	2125 Lumens
17	17" Diameter x 3.75" Height	25 Watt	2000 Lumens	2250 Lumens	2125 Lumens

#### **SELECTABLE CCT FEATURE -**



Selectable CCT Built-in dip switch on LED board allows the user to manually change the CCT: 3000K / 4000K / 5000K

