

Lewis 2

Ceiling or Wall Mount Luminaire Optional Emergency Battery / Motion Sensor Wet Location Rated

We reserve the right to revise the design or components of any product without notice.

CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		

SPECIFICATIONS

- DRIVER — Universal Voltage 120/277v Electronic Driver.
- DIFFUSER — High Transmission Opal Polycarbonate for evenly diffused light distribution.
- EMERGENCY BATTERY — Optional Integral Emergency Battery.
- HOUSING — Injection Molded Polycarbonate Housing.
- LIGHT ENGINE — Energy Efficient LED. >80CRI.
- MOTION SENSOR — Optional Integral Occupancy Motion Sensor.
- COMPLIANCE — Built to comply with U.S. and Canadian safety standards.
ETL/cETL Listed, and Energy Star Compliant. Wet Location Rated.
- WARRANTY — 5-Year Limited Warranty on Driver/LED Module.



ORDERING INFO

ORDERING GUIDE:	Series	Wattage	CCT	Voltage	Finish	Options

SERIES

LW2 = Lewis 2 Series

WATTAGE

LED23 = 23 Watt LED
— 2100 Lumens (Based on 3000K) | 94.5 LPW

COLOR TEMPERATURE (CCT)

3K = ±3000K range LED
35K = ±3500K range LED
4K = ±4000K range LED
5K = ±5000K range LED

VOLTAGE

UNV = Universal Voltage (120-277V) Electronic Driver

STANDARD FINISH

WH = White Finish

SENSOR CONTROL (Sensor Integral to Fixture)

OCC = Occupancy Sensing | Motion Sensor Integral

EMERGENCY BATTERY OPTIONS

EL = Emergency Battery Backup

DIMENSIONS/WATTAGES

