

MRC3

Multi-Purpose Round Ceiling Luminaire Low Profile and 5 CCT Selectable ETL Listed / Wet Location

We reserve the right to revise the design or components of any product without notice.

CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		

SPECIFICATIONS

- DRIVER — 120 Volt Driver with TRIAC dimming.
- DIFFUSER — Polystyrene diffuser.
- HOUSING — ABS Thermoplastic housing.
- LIGHT ENGINE — Energy Efficient LED with Selectable 5 CCTs (>90CRI).
- LIFETIME — 50,000 Hours
- MOUNTING — Ceiling Mount.
- COMPLIANCE — Built to comply with U.S. and Canadian safety standards.
ETL Listed, Energy Star compliant, and suitable for wet locations.
- WARRANTY — 5-Year Limited Warranty.



ORDERING INFO

	Series	Size	Wattage	CCT	Voltage	Finish	Options
ORDERING GUIDE:							

SERIES

MRC3 = Multi-Purpose Round Ceiling Luminaire 3 Series

SIZE

7 = 7.32" Diameter x 0.95" Depth

LED WATTAGE

LED15 = 15 Watt LED (1000 Lumens)

COLOR TEMPERATURE (CCT)

SCCT = *Selectable CCT: 2700K | 3000K | 3500K | 4000K | 5000K

**Note: Fixtures will ship from factory at the warmest CCT setting. It is the installer's responsibility to set the fixture at the desired CCT for their project.*

VOLTAGE

120 = 120 Volt Driver (TRIAC Dimmable)

FINISH

WH = White Finish

DIMENSIONS

