Nicole DECORATIVE SURFACE SERIES

Indoor Wall Family—DRY LOCATION Wall Mount Decorative Luminaire

We reserve the right to revise the design or components of any product without notice.

CATALOG #	TYPE
PROJECT/LOCATION	
APPROVED BY	



SPECIFICATIONS

- DIFFUSER .020" matte acrylic with decorative pattern.
- DRIVER Constant Current.
- FINISH An enclosed shield sconce with splatter panel. See Options for Shield Finish.
- HARDWARE INCLUDED (1) J Boxstrap, (1) Nipple, (1) Cap Nut
- LAMP Super-Bright White LED INCLUDED, Compact Fluorescent (DTT)
- LUMENS Initial lumen values of super-bright LEDs degrade over time based on several factors including, and not limited to, ambient temperatures of the board they are inserted into, the effects of heat sinking, the ambient conditions of the fixtures and the environment the fixture is used in.
- MOUNTING Lens mounts to housing with top and bottom screws.
- POWER FACTOR Electronic Driver
- UL/ULC Listed to U.S. and Canadian safety standards.





LAMP TYPE/QTY/WATTAGE ¹⁰			
Fixture		Nicole	
Dimensions - W x H x D		11" x 11¾" x 4"	
Compact Fluorescent Double Twin Tube		(1)13/18w, (2)13w	
Light Emitting Diode LED		20w	



ORDERING GUIDE:

LAMP/QTY/WATT

COLOR TEMP

VOLTAGE/POWER FACTOR

SHIELD FINISH

OPTIONS

NOTES:

- Consult Factory with requests regarding lamp sources, wattages or voltages not shown.
- 3 Consult Factory for additional **Emergency Battery options** not shown.

SERIES

NI = Nicole Series

LAMP TYPE/LAMP QUANTITY/WATTAGE Refer to Above Chart

LED COLOR TEMP

3K = 3000 K range

4K = 4000 K range **5K** = 5000 K range

6K = 6000 K range

VOLTAGE

120 = 120 Volts

SHIELD FINISH

CC-BL = Blue Lapis

CC-BS = Blood Stone **CC-CS** = Copper Silver Swirl

CC-DR = Desert Rose CC-GM= Green Malachite

CC-HC = Hammered Copper

CC-JA = Jadeite

CC-MH= Mahogany

CC-OB = Ocean Blue

CC-TI = Tiger Iron

OPTIONS

DIM = Dimming Driver (Consult Factory)

EMERGENCY OPTIONS

REL2 = Remote Emergency Battery

TTT; 1-2 Lamp; 650 Lumens

