GALILEO FAMILY-CR628 Series-Custom Saturn

SPECIFICATIONS:

- BALLAST For TT, T5, T8 Fluorescent Electronic (EB) cold weather 0°C is Standard. For HID HPF is Standard. For MH Pulse Start is Standard, EBMH Standard.
- BACKPLATE 16 Ga. aluminum (AL)
- BACKBOX 16 Ga. aluminum (AL) with wire access on four sides and back through 7/8" dia. KO flattened water tight (Optional for surface conduit entry; standard with emergency battery)
- DIFFUSER White translucent, fully enclosed non-yellowing 100% virgin acrylic, .125 Thick (1/8"). Optional Clear (CTB) or Opaque (OQTB) top and/or bottom. Optional Open (ONTB) top and/or bottom — Dry Location Only.
- PERFEX PX: Perforated Alu Panel Insert with 1/16" dia. holes. Specify Finish.
- FINISH Corrosion and Weather resistant, extremely durable pre-treated oven baked polyester powder
- GASKETING High temp., non-aging black EPDM and/or neoprene rubber around the entire lens perimeter & rear wire entrance hole to protect against dust, moisture, outside contaminants
- FASTENERS— Stainless steel tamperproof screws ---(2) To secure lens in place
- MOUNTING Use (4) 5/16" dia. holes for 1/4" dia. bolts for outdoor or indoor (no center access hole for J-Box mount).
- UL/ULC Listed to U.S. and Canadian safety standards Suitable for wet locations.
- WALL WASH For wall wash patterns specify: Uplight, Downlight or both: MHU (Uplight) or MHD (Downlight) or MHUD (Up and Downlight) LEDU (Uplight) or LEDD (Downlight) or LEDUD (Up and Downlight)



