SONAR

DECORATIVE INDOOR WALL SCONCE Elegant Contoured Design

We reserve the right to revise the design or components of any product without notice.

CATALOG #	TYPE
PROJECT/LOCATION	
APPROVED BY	

SPECIFICATIONS

- DIMNSIONS Small: 13.5"H x 5"W x 5"D (4.75"Dia. Cover)
 Large: 21"H x 5.5"W x 5"D (4.75"Dia. Cover)
- DRIVER 120 Volts.
- HOUSING Durable cold rolled steel.
- FINISH Powder Coat Finish applied over pre-treated surfaces.
- LIGHT ENGINE Energy Efficient LED. Incandescent (INC) A15/ A19 Base Sockets allow you to add your own LED or Incandescent Light Bulbs - Max 40W.
- MOUNTING Wall mounted via universal J-Box strap.
- COMPLIANCE Built to comply with U.S. and Canadian Safety Standards. Suitable for Indoor Locations.

APPLICATIONS

- RESTAURANTS & DINING
- FOYERS & HALLWAYS
- RETAIL & COMMERCIAL
- HOSPITALITY

GRAVURA GRAPHICS



White Vein (WVN)



Gold Marble (GMB)





Travertine (TVT)



LED BULBS



Incandescent (INC) Sockets Allow You To Add Your Own Standard A15 / A19 Base LED or Incandescent Light Bulbs [Max 40W]

ORDERING GUIDE:	Series	Size LED Wa	ttage Color	Voltage	Finish	Options	
	SERIES SN = Sonar Series		VOLTA 120	AGE = 120 Volts			
	 SIZE S = Small 13.5"H x 5"W x 5"D (4.75"Dia. Cover) L = Large 21"H x 5.5"W x 5"D (4.75"Dia. Cover) LED WATTAGE LED10 = 10 Watt LED - 800 Initial Lumens (Hardwired) INC = Incandescent A15 (For Small) or A19 Socket (For Large) Sockets — Add Your Own LED or Incandescent Light Bulbs - Max 40W 		BK WH	FINISH BK = Black WH = White *Additional Gravura Graphic Finishes Available - Consult Factory OPTIONS Consult Factory			
			rge) Sockets				
	LED COLOR TEMPERATU	JRE					

- **3K** = ±3000K range LED
- **4K** = ±4000K range LED
- $5K = \pm 5000K$ range LED

