

# Post Top Decorative

## Area/Parking/Industrial

LED, INDUCTION

Low Light Pollution Design - Full Cut-Off



**ARRA**  
Compliant

We reserve the right to revise the design or components of any product without notice.


CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		



### SPECIFICATIONS

- **BALLAST** — High Power Factor, Low THD Replaceable Electronic Ballast made with long life components.
- **COLOR TEMPERATURE** — Correlated Color Temp of 5000°K for greater visibility.
- **GASKETING** — Concealed continuous gasket seals against harmful dust, dirt, moisture and insects.
- **HOUSING** — Die-cast aluminum with electrocoat black paint.
- **LAMP** — Induction Lamp. Instant ON flicker-free Cold Start and Hot Re-Start. Advanced phosphors for high Lumen Maintenance and high lumen output. LED.
- **LENS** — Heat and Impact resistant tempered polycarbonate lens.
- **LIGHT SENSOR** — Optional Light Sensor for Dusk-to-Dawn ON/OFF control — Photocell (#9206 or #9221)
- **SIZE** — 16" wide x 30" long
- **UL/ULC Listed** to U.S. and Canadian safety standards. Suitable for wet locations.

LAMP TYPE/QTY/WATTAGE <sup>1</sup>		
Fixture	Post Top Decorative	
Dimensions	16" wide x 30" long (nominal)	
QL Induction <sup>3</sup> <i>Up to 100,000 HR Lamp Life</i>	QL	55, 85 Watt
Light Emitting Diode	LED	75 Watt (nominal)



### ORDERING GUIDE:

<b>SERIES</b>	<b>LAMP TYPE/QTY/WATT</b>	<b>COLOR TEMP</b>	<b>VOLTAGE</b>	<b>FINISH</b>	<b>OPTIONS</b>
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

#### NOTES:

- Consult Factory with requests regarding lamp sources, including LED, color temp., wattages or voltages not shown.
- Lamping system is warranted by MFR for 40,000 HOURS.

#### SERIES

**PTD** = Post Top Decorative Series

#### LAMP TYPE/QUANTITY/WATTAGE

Refer to Above Chart

#### COLOR TEMP (LED, Induction)

- 3K** = ±3000K range Induction Only
- 4K** = ±4000K range Induction Only
- 5K** = ±5000K range LED or Induction

#### VOLTAGE:

- 120** = 120 Volt (**Induction**)
- 277** = 277 Volt (**Induction**)
- EBU** = Universal Voltage (120 thru 277v) (**LED**)

#### FINISH

**BK** = Black Finish

#### LED OPTIONS

- BL** = Dual Circuit Bi-Level Lighting Switched High/Low
- MS** = Motion Sensor
- SG** = 10KA Surge Protection for LED fixtures (meets ANSI spec C62.41.2)

#### OPTIONS

- 9206** = Photocell – 120V
- 9221** = Photocell – 277V