

# Post Top Lantern

## Area/Parking/Industrial

We reserve the right to revise the design or components of any product without notice.



**ARRA**  
Compliant


CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		



### SPECIFICATIONS

- BALLAST — Integral ballast in bottom of luminaire
- HOUSING — Die-cast aluminum housing.
- FINISH — Powder Coat Paint Finish
- LENS FASTENERS — Stainless steel latch to secure canopy.
- REFRACTOR — Acrylic Textured Refractor is Standard (TAR).  
Optional Polycarbonate Textured Refractor (TPR).
- LAMP — Super Bright White Light Emitting Diode (LED)
- REFLECTOR — Sky White Reflector
- SIZE — 16<sup>3</sup>/<sub>4</sub>" wide x 27<sup>1</sup>/<sub>4</sub>" long
- UL/ULC Listed to U.S. and Canadian safety standards.  
Suitable for wet locations.

LAMP TYPE/QTY/WATTAGE <sup>1</sup>		
Fixture	Post Top Lantern	
Dimensions	16 <sup>3</sup> / <sub>4</sub> " wide x 27 <sup>1</sup> / <sub>4</sub> " long (nominal)	
QL Induction <sup>4</sup> <i>Up to 100,000 HR Lamp Life</i>	QL	55, 85 Watt
Light Emitting Diode	LED	30, 55, 75, 90 Watt (nominal)



### ORDERING GUIDE:

SERIES	LAMP TYPE/QTY/WATT	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

#### NOTES:

- Consult Factory with requests regarding lamp sources, including LED, color temp., wattages or voltages not shown.
- Lamping system is warranted by MFR for 40,000 HOURS.

#### SERIES

PTL = Post Top Lantern Series

#### LAMP TYPE/QUANTITY/WATTAGE

Refer to Above Chart

#### COLOR TEMP (LED, Induction)

- 3K = ±3000K range Induction Only
- 4K = ±4000K range Induction Only
- 5K = ±5000K range LED or Induction

#### VOLTAGE

- 120 = 120 Volt (Induction)
- 277 = 277 Volt (Induction)
- EBU = Universal Voltage (LED)  
(120 thru 277v)

#### FINISH

BK = Black Finish

#### OPTIONS

- 9206 = Integral Photocell 120v
- 9221 = Integral Photocell 277v
- TPR = Textured Polycarbonate Refractor

#### LED OPTIONS

- BL = Dual Circuit Bi-Level Lighting  
Switched High/Low
- MS = Motion Sensor
- SG = 10KA Surge Protection  
(meets ANSI spec C62.41.2)