

# Post Top Refractive Area/Parking/Industrial



**ARRA**  
Compliant

We reserve the right to revise the design or components of any product without notice.


CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		



## SPECIFICATIONS

- **BALLAST** — High Power Factor, Low THD Replaceable Electronic Ballast made with long life components.
- **COLOR TEMPERATURE** — Correlated Color Temp of 5000°K for greater visibility.
- **GASKETING** — Concealed continuous gasket seals against harmful dust, dirt, moisture and insects.
- **HOUSING** — Die-cast aluminum with electrocoat black paint.
- **LAMP** — Super Bright White LED.
- **LENS** — Heat and Impact resistant tempered polycarbonate lens.
- **LIGHT SENSOR** — Optional Light Sensor for Dusk-to-Dawn ON/OFF control — Photocell (#9206 or #9221)
- **UL/ULC Listed** to U.S. and Canadian safety standards. Suitable for wet locations.

LAMP TYPE/QTY/WATTAGE <sup>1</sup>		
Fixture		Post Top Refractive
QL Induction <sup>4</sup> <i>Up to 100,000 HR Lamp Life</i>	QL	55, 85 Watt
Light Emitting Diode	LED	75 Watt (nominal)



## ORDERING GUIDE:

SERIES	LAMP TYPE/QTY/WATT	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
--------	--------------------	------------	---------	--------	---------

### NOTES:

- Consult Factory with requests regarding lamp sources, including LED, color temp., wattages or voltages not shown.
- Lamping system is warranted by MFR for 40,000 HOURS.

### SERIES

**PTR** = Post Top Refractive Series

### LAMP TYPE/QUANTITY/WATTAGE

Refer to Above Chart

### COLOR TEMP (LED, Induction)

- 3K** = ±3000K range Induction Only
- 4K** = ±4000K range Induction Only
- 5K** = ±5000K range LED or Induction

### VOLTAGE

- 120** = 120 Volt (**Induction**)
- 277** = 277 Volt (**Induction**)
- EBU** = Universal Voltage (120 thru 277v) (**LED**)

### FINISH

- BK** = Black Finish

### LED OPTIONS

- BL** = Dual Circuit Bi-Level Lighting Switched High/Low
- MS** = Motion Sensor
- SG** = 10KA Surge Protection (meets ANSI spec C62.41.2)

### OPTIONS

- 9206** = Photocell – 120V
- 9221** = Photocell – 277V