

572-N • 574-N

Vandal Resistant Narrow Linear Fixture

SELECTABLE LED WATTAGE / CCT SERIES

Wet Location (Covered Ceiling)

We reserve the right to revise the design or components of any product without notice.

CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		

SPECIFICATIONS

- APPLICATIONS — Stairwells, Locker Rooms, Corridors, Hallways, Lavatories.
- DRIVER — Universal volt (120-277v) electronic driver.
- FASTENERS — Flat head stainless steel torx screws.
- FINISH — Polyester powder coated finish.
- HOUSING — Aluminum housing and heatsink.
- LENS — Polycarbonate translucent lens for uniform light distribution.
- LIGHT ENGINE — Energy Efficient LED - Selectable Wattage / CCT.
- MOUNTING — Surface mount to ceiling J-BOX via pre-cut mounting holes or pendant mount with two stems and swivel canopies.
- COMPLIANCE — Built to comply with U.S. and Canadian Safety Standards.
ETL listed and CE, CB, SAA, Buy American Act (BAA) compliant.
Surface ceiling mount is suitable for indoor wet locations (covered ceiling), wall and pendant mount are for indoor damp locations only.
- WARRANTY — 5-year Limited Warranty.



ORDERING INFO - SELECTABLE WATTAGE/CCT SERIES

Series	Mounting	Wattage	CCT	Voltage	Finish	Options

SERIES

572-N = 572 Narrow 2-Foot LED Linear Series
574-N = 574 Narrow 4-Foot LED Linear Series

MOUNTING

SM = Surface Ceiling Mount
PEND = Pendant Mount

- 12" Stem is Standard (2 Per Fixture)
- For Other Stem Lengths (Consult Factory)
- Choose Pendant Canopy Style:**
 - SWC-RR = Swivel Canopy for 4" Round J-Box
— Rapid Mount with Hinged Door
 - SWC-SR = Swivel Canopy for 4" Square J-Box
— Rapid Mount with Hinged Door

WATTAGE

SLED = *Selectable LED Wattage
— 2-Foot: 20W | 30W | 40W
— 4-Foot: 35W | 42W | 50W

COLOR TEMPERATURE (CCT)

SCCT = *Selectable CCT: 3000K | 4000K | 5000K

**Note: Fixtures will ship from factory at lowest wattage and warmest CCT. It is the installer's responsibility to set the fixture at the desired wattage and CCT for their project.*

VOLTAGE

UNV = Universal Volt (120-277v) Electronic Driver
— Non-Dimmable

STANDARD FINISH

WH = White Finish

PREMIUM UPCHARGE FINISH

BK = Black Finish
BZ = Bronze Finish
SGR = Silver Gray Finish
CC = Custom Color (Visit www.ralcolor.com)
— Provide RAL# or Make-to-Match Color Chip

BACK BOX OPTIONS

BBX2 = Back Box for 2-Foot
BBX4 = Back Box for 4-Foot

SENSOR OPTIONS

OCC = Occupancy Sensing | Motion Sensor Integral ²⁰
— Standby Dim Level Presets: ON/OFF (0%/100%)

EMERGENCY BATTERY OPTIONS

EL10W = Integral 10 Watt Emergency Battery

MISC OPTIONS

TDM = Tandem Joined Fixtures ²

NOTES:

- ² Backbox (BB) Required.
- ²⁰ Max mounting height is 18' (18 feet).

572-N • 574-N

Vandal Resistant Narrow Linear Fixture

STATIC LED WATTAGE / CCT SERIES

Wet Location (Covered Ceiling)

We reserve the right to revise the design or components of any product without notice.

CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		

SPECIFICATIONS

- APPLICATIONS — Stairwells, Locker Rooms, Corridors, Hallways, Lavatories.
- DRIVER — Universal volt (120-277v) electronic driver.
- FASTENERS — Flat head stainless steel torx screws.
- FINISH — Polyester powder coated finish.
- HOUSING — Aluminum housing and heatsink.
- LENS — Polycarbonate translucent lens for uniform light distribution.
- LIGHT ENGINE — Energy Efficient LED - Static Wattage / CCT.
- MOUNTING — Surface mount to ceiling J-BOX via pre-cut mounting holes or pendant mount with two stems and swivel canopies.
- COMPLIANCE — Built to comply with U.S. and Canadian Safety Standards.
ETL listed and CE, CB, SAA, Buy American Act (BAA) compliant.
Surface ceiling mount is suitable for indoor wet locations (covered ceiling),
wall and pendant mount are for indoor damp locations only.
- WARRANTY — 5-year Limited Warranty.



ORDERING INFO - STATIC WATTAGE/CCT SERIES

Series	Mounting	Wattage	CCT	Voltage	Finish	Options

SERIES

572-N = 572 Narrow 2-Foot LED Linear Series
574-N = 574 Narrow 4-Foot LED Linear Series

MOUNTING

SM = Surface Ceiling Mount
PEND = Pendant Mount
— 12" Stem is Standard (2 Per Fixture)
— For Other Stem Lengths (Consult Factory)
Choose Pendant Canopy Style:
SWC-RR = Swivel Canopy for 4" Round J-Box
— Rapid Mount with Hinged Door
SWC-SR = Swivel Canopy for 4" Square J-Box
— Rapid Mount with Hinged Door

WATTAGE

Note: Refer to Below Chart for Size / Wattage Compatibility
LED(xx) = LED (xx = Wattage, ex: LED40)

COLOR TEMPERATURE (CCT)

3K = ±3000K range LED
35K = ±3500K range LED
4K = ±4000K range LED
5K = ±5000K range LED

VOLTAGE

UNV = Universal Volt (120-277v) Electronic Driver
— 0-10V Dimming (100-30%) is Standard

STANDARD FINISH

WH = White Finish

PREMIUM UPCHARGE FINISH

BK = Black Finish
BZ = Bronze Finish
SGR = Silver Gray Finish
CC = Custom Color (Visit www.ralcolor.com)
— Provide RAL# or Make-to-Match Color Chip

BACK BOX OPTIONS

BBX2 = Back Box for 2-Foot
BBX4 = Back Box for 4-Foot

CONTROL OPTIONS (Choose from Manual or Sensor)

MANUAL CONTROL (Wall Switch or Control System)

Note: Cannot be used with Sensor Controls

Note: 0-10V (100-30%) Dimming is Standard

D7A = 0-10VDC LED Dimming Driver (100-10%)

D7B = 0-10VDC LED Dimming Driver (100-1%)

OR

Sensor Control (Sensor Integral to Fixture)

Note: Cannot be used with Manual Controls

OCC = Occupancy Sensing | Motion Sensor Integral ²⁰
— Standby Dim Level Presets: ON/OFF (0%/100%)

BLD = Bi-Level Dimming | Motion Sensor Integral ²⁰
— Standby Dim Level Presets:

10% / 20% / 30% (Standard) / 50%

EMERGENCY BATTERY OPTIONS

EL10W = Integral 10 Watt Emergency Battery

MISC OPTIONS

TDM = Tandem Joined Fixtures ²

ACCESSORY OPTIONS (order as a separate line)

REMT0019 = Remote Controller for BLD Sensor Option

Fixture		572-N	574-N
Light Emitting Diode	LED	20W / 30W / 40W	30W / 40W / 50W

NOTES:

² Backbox (BB) Required.

²⁰ Max mounting height is 18' (18 feet).



572-N • 574-N

Vandal Resistant Narrow Linear Fixture
Selectable or Static LED Wattage / CCT
Wet Location (Covered Ceiling)


We reserve the right to revise the design or components of any product without notice.

CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		


DIMENSIONS



BACK BOX OPTION



PENDANT MOUNT



Swivel Canopy 4"
for Round/Octagonal J-BOX
(PEND-SWC-RR)




Swivel Canopy 4"
for Square J-BOX
(PEND-SWC-SR)

PHOTOMETRIC DATA

Summary of Results 574-N-LED42-4K-UNV					
Lumen Output	Eff cacy	Input Power	CCT	Distribution	BUG Rating
5,668.6 Lumens	129.4 Lm/W	43.79W	4000K	Type VS	B2-U3-G2

LCS Summary	
Zone	Lumens
Forward Low (0-30)	680.6
Forward Medium (30-60)	1309.1
Forward High (60-80)	551.0
Forward Very High (80-90)	114.2
Back Low (0-30)	683.9
Back Medium (30-60)	1323.6
Back High (60-80)	560.6
Back Very High (80-90)	117.1
Up Low (90-100)	116.5
Up High (100-180)	212.0



572-N • 574-N

Vandal Resistant Narrow Linear Fixture
Selectable or Static LED Wattage / CCT
Wet Location (Covered Ceiling)

We reserve the right to revise the design or components of any product without notice.

CATALOG #		TYPE
PROJECT/LOCATION		
APPROVED BY		

ELECTRICAL DATA _____

572-N 2-Foot LED Linear (Selectable Wattage / CCT)					
Published Wattage	Color Temp (CCT)	Wattage (120V)	Amps (120V)	Wattage (277V)	Amps (277V)
40W	5000K	42.7W	0.35	41.0W	0.15
40W	4000K	40.6W	0.33	39.0W	0.14
40W	3000K	41.9W	0.34	40.3W	0.15
30W	5000K	34.2W	0.28	33.3W	0.12
30W	4000K	32.8W	0.26	32.0W	0.12
30W	3000K	33.8W	0.27	33.0W	0.12
20W	5000K	26.1W	0.21	25.9W	0.09
20W	4000K	25.2W	0.20	25.0W	0.09
20W	3000K	25.9W	0.21	25.6W	0.09

574-N 4-Foot LED Linear (Selectable Wattage / CCT)					
Published Wattage	Color Temp (CCT)	Wattage (120V)	Amps (120V)	Wattage (277V)	Amps (277V)
50W	5000K	52.8W	0.43	50.8W	0.18
50W	4000K	50.6W	0.41	48.7W	0.15
50W	3000K	52.9W	0.43	50.9	0.13
42W	5000K	41.6W	0.34	40.7W	0.14
42W	4000K	40.1W	0.32	39.2W	0.14
42W	3000K	41.7W	0.34	40.7W	0.15
35W	5000K	36.1W	0.29	35.4W	0.13
35W	4000K	34.8W	0.28	34.2W	0.13
35W	3000K	36.1W	0.29	35.4W	0.13